

WHAT IS CLAIMED IS:

- 5
1. A thin film formation apparatus comprising:
a head portion having an ultrasonic oscillator; and
a nozzle filled with an application liquid for forming an EL layer.
- 10
2. A thin film formation apparatus comprising:
a head portion having an ultrasonic oscillator; and
a nozzle filled with an application liquid for forming an EL layer,
wherein said nozzle has a heater.
- 15
3. A thin film formation apparatus according to claim 2, wherein said nozzle has a
large internal diameter portion and a small internal diameter portion, and
said heater is formed in said small internal diameter portion.
- 20
4. A thin film formation apparatus according to claim 2, wherein the small internal
diameter portion of the nozzle has a contact element.
5. A thin film formation apparatus according to claims 1 or 2, wherein said
application liquid in said nozzle is pressurized by ultrasonic oscillations, and is pushed out
from said nozzle.
- 7
6. A method of manufacturing a self-light-emitting device, comprising the steps of:
filling a nozzle with an application liquid for forming an EL layer; and
applying said application liquid to a pixel column in accordance with applying
- Sub
PS

ultrasonic oscillations or heat.

7. A method of manufacturing a self-light-emitting device according to claim 6,

wherein:

said nozzle has a large internal diameter portion and a small internal diameter

portion;

said small internal diameter portion has a heater; and

said heater applies heat to the application liquid filling the nozzle.

8. A method of manufacturing a self-light-emitting device, comprising the steps of :

imparting ultrasonic oscillations to a nozzle of a head portion by using an ultrasonic oscillator; and

imparting ultrasonic oscillations to an application liquid filling said nozzle by using said ultrasonic oscillator.

9. A method of manufacturing a self-light-emitting device according to claim 8, wherein a heater of said nozzle applies heat to said application liquid filling said nozzle.

10. A method of manufacturing a self-light-emitting device according to claims 6 or 8, wherein said application liquid is pushed out from said nozzle in accordance with pressurization, and is applied.

11. A method of manufacturing a self-light-emitting device according to claims 6 or 8, wherein said application liquid is pushed out from said nozzle in accordance with: capillary

action; the weight of said application liquid; or pressure; and is applied.

12. A method of manufacturing a self-light-emitting device according to claims 6 or 8, wherein said application liquid filling said nozzle is applied in accordance with a contact element of said nozzle contacting a bank.

Sub 7
A2
encl

1.020300 " 2.7134.54

add
A27

add
p27